

Lindau LV

Art der Herstellung	Needlefelt		ISO 2424
Oberflächenstruktur	Flat		ISO 2424
Rücken	LV		ISO 2424
Nutzschicht	100% PP		
Polgewicht	630 g/m ²		
Gesamtgewicht	790 g/m ²	+/- 10%	ISO 8543
Gesamthöhe	4,5 mm	+/- 10%	ISO 1765
Beanspruchungsbereich	Commercial 33, Areas with heavy use		EN 1307
Komfortklasse	LC1		EN 1307
Stuhlrolleneignung	Yes, permanent use		EN 985
Treppeneignung	Yes, incidental use		EN 1307
Lichteinheit	≥ 5		ISO 105-B02
Reibechtheit, trocken & nass	≥ 4		ISO 105-X12
Wasserechtheit	≥ 4		ISO 105-E01
Maßstabilität	Shrinkage ≤ 1,2 %		ISO 2551
	Extension ≤ 0,5 %		ISO 2551
Elektrostatische Aufladung	< 2kV		ISO 6356
Wärmedurchlasswiderstand R und λ	0,07 m ² .K/W		ISO 8302
Gleitwiderstand	> 0,3	Machine direction	EN 13893
	> 0,3	Crossdirection	EN 13893
Brandverhalten	Cfl,s1		EN 13501-1
Prodis-ID (GuT)	E1146BAA		www.pro-dis.info
AbZ Nr.	Z-156.601-703		

Floorsymbols



Certificates

Vebe PP / 334 / L

Z-156.601-703



Textiles & Flooring Institute GmbH

Emissionsgeprüfter Bodenbelag
nach DIBt-Grundsätzen

EN 14041

CE

Reaction to fire:
Cfl,s1

Slip resistance:
DS

DOP:
1061#91LV00
Textile Floorcovering
EN1307



Vebe Floorcoverings b.v. certifies the supplied products to meet the requirements as specified and stated in the last editions of the technical information. The products have been produced and tested according procedures agreed in our quality system (according ISO 9001). The tests have been carried out according to the prescribed standards.