

ToLEDo GLS

ToLEDo GLS 850LM 865 E27 SL

0026629



Range Features

-

PRODUCT OVERVIEW

Lamp finish	Frosted
Lamp shape	A60
Colour temperature (K)	6500
CRI (Ra)	80
Dimmable	No
EAN code	5410288266299
Energy class	A+
Equivalent watt (W)	63
Cap/Base	E27
Watt (Nominal) (W)	10
Light colour	Daylight
Ordering number	0026629
Efficacy (Rated) (lm/w)	85
Average life (Rated) (h)	15000
Luminous flux (Rated) (lm)	850
Technology	LED
Voltage (V)	220-240
Colour consistency (SDCM)	6

DATA TABLE

General data

Average life (Nominal) (h)	15000
Control gear required	No
Lamp finish	Frosted
Lamp shape	A60
Dimmable	No
Dry applications use only	Yes
EAN code	5410288266299

ToLEDo GLS

ToLEDo GLS 850LM 865 E27 SL

0026629

Energy class	A+
Energy saving lamp	Yes
General application	Hospitality; Residential & Consumer
Intended purpose	No
Cap/Base	E27
Lamp mercury content (mg)	0
No. of switching cycles before premature failure (min)	50000
Optimal operating condition (°C)	25
Ordering number	0026629
Product name	ToLEDo GLS 850LM 865 E27 SL
Average life (Rated) (h)	15000
Special purpose lamp	No
Starting time (max) (s)	0.05
Technology	LED
Transformer required	No
Warm-up time to 60% of full light (max) (s)	< 1s => 60%

Optical data

Colour temperature (K)	6500
CRI (Ra)	80
Light colour	Daylight
Lumen maintenance at end of nominal life (%)	70
Luminous flux (Nominal) (lm)	850
Luminous flux (Rated) (lm)	850
Suitable for accent lighting	No
Adjustable chromaticity	No
Colour consistency (SDCM)	6

Electrical data

Drive current (mA)	79
Equivalent watt (W)	63
kWh per 1000 hours burning time	10
Lamp power factor	0.5
Watt (Nominal) (W)	10
Efficacy (Rated) (lm/w)	85
Watt (Rated) (W)	10
Voltage (V)	220-240

Physical data

Max. Lamp Diameter (mm) - D	60
------------------------------------	----

ToLEDo GLS

ToLEDo GLS 850LM 865 E27 SL

0026629

Lamp Length (mm) - C/L	109
Lamp dimension equal to filament lamp equivalent	Yes

TECHNICAL DRAWINGS

